

Kenai Peninsula Racing Lions



Late Model Rules

Updated 2024

10 LATE MODEL

10.1 FRAME

- Frame type is optional.
- Minimum wheelbase of 104 inches.
- Both tubular and stock stub front ends will be allowed.
- All cars will have to meet a minimum weight requirements of 2500 pounds.
- This weight includes a full load of fuel with the driver.
- All frames must meet all A.C.T.A. safety rules and inspections.

10.2 BODY

- Bodies are mandatory and must be metal.
- Aftermarket bodies are approved.
- Fiber glass hoods and roof are approved.
- No open wheel cars allowed.
- Tires may not extend from the body more than 6 inches on either side.
- Body must be securely fastened to the frame and roll cage.
- All spoilers to be a maximum 10 inches high.
- Stock steel bodies, if used must be from a 1986 or newer American made automobile.
- They may be altered to aid in securing them to the frame and roll cage.

10.3 FIREWALL

- Must be stock or a minimum of 24-gauge steel.
- They must provide full protection between the engine and driver's compartment.
- Holes and openings in the firewall must be sealed.
- All hoods, deck lids and doors must be securely fastened.
- All chrome, lenses, wood, upholstery, and glass must be removed.
- Driver must obtain access through the window.
- Seat must be mounted on the left side of the driveline.

10.4 BUMPERS

- Bumpers are optional, but highly recommended.
- Round pipe or square tubing may be a maximum of 2" O.D.
- Wall size of either square or round tubing must not be less than .095" or a maximum of .140" in thickness.

10.5 ENGINES

- Engines must be American made.
- No Aluminum blocks.
- Heads optional.
- No blowers or super-charging.
- Minimum distance of setback is 72 inches measured from the center of rear axle tube to the rear of block bell housing mounting surface.

10.6 IGNITION

- Ignition type is optional.
- Cars must have a kill switch clearly marked.
- The switch must be within the drivers reach and easy to reach from the outside of the car.
- Electric fuel pumps must be wired into an oil pressure safety switch.

10.7 FUEL

- Approved fuel cell required.
- Maximum 32 gallons. Pump gas, aviation fuel, or methanol permitted.
- No nitrous.
- One carburetor.
- No injections, blowers or super charging.

10.8 TRANSMISSION/DIFFERENTIAL

- Transmissions are mandatory and must have one forward and reverse gear.
- No transmission or oil coolers allowed in the driver's compartment.
- A S.E.M.A. approved scatter shield must be used for manual transmission.
- Differential type is optional.

10.9 STEERING

- Steering type is optional.
- No front straight axles.
- No four wheel or front wheel drives allowed.

10.10 TIRES/WHEELS

- Wheels must be approved racing type or safety reinforced on all four corners of the car.
- No carbon fiber or plastic wheels allowed.
- Maximum wheel size will be 14 inches. (Bead to bead)